



STANDARD FEATURES

- Axle based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Oscillating axle
- Drivable at full height
- EasyDrive[™] direction sensing drive and steer controls
- SpeedyReach™ functionality
- SkyRiser™ functionality
- 360° Continuous turret rotation
- 45% Gradeability
- Secondary guarding (SGE)
- Deutz TD2.9 Diesel engine
- Swing out engine tray
- Swing up cowlings
- Modular platform railing system
- Tri-entry sliding mid-rails
- Wiring for AC outlet to platform
- Proportional controls
- Relay based control system
- Colour coded and numbered wiring
- Hourmeter
- Operator horn
- Overload sensing system
- Tie down/lifting lugs
- Wet disc SAHR brakes (front and rear axle)
- 18 x 625 Grip lug foam-filled tyres

ACCESSORIES AND OPTIONS

- 0.91 x 2.44 m Platform
- 3.5 kW Generator (includes hydraulic oil cooler)
- Cold weather start kit (includes cold start engine oil, battery blanket, and hydraulic tank heater)
- Arctic weather package (includes arctic engine oil, battery blanket, hydraulic tank heater, block heater, arctic hydraulic oil, arctic platform rotator and arctic gear oil in the axels and swing drive. Glow plugs, arctic hydraulic hoses (all), and oversized foot switch cover are also included (standard equipment).
- Hydraulic oil cooler
- Flashing light
- 12.7 mm (1/2") Airline to platform
- Positive air shut-off valve
- Hostile environment package (Includes cylinder bellows, boom wipers, covers for the fly boom cutouts, and control box cover)
- Auxiliary top rail (0.91 x 2.44 m platform only)
- Control box cover
- Platform work lights
- All motion alarm
- Pipe rack
- Tool caddy
- Rear gate
- Bio oil

TIRE OPTIONS


Grip lug foam-filled non marking tyres


Capacities, and machine weights may differ when options are added.




SJ85 AJ ARTICULATING BOOM

Dimensions	SJ85 AJ
Work Height	27.91 m
Platform Height	25.91 m
Horizontal Reach	17.07 m
Up and Over Height	10.36 m
A Platform Size	0.91 x 1.83 m
B Stowed Width	2.49 m
C Tailswing	0.91 m
D Stowed Height	2.67 m
E Transportation Height	2.90 m
F Stowed Length	11.63 m
G Transportation Length	10.00 m
H Wheelbase	2.84 m
I Ground Clearance	0.34 m
Specifications	SJ85 AJ
Rotation	360°
Platform Rotation	170°
Jib Length	1.68 m
Jib Range +/-	+65°/-60°
Weight	16,965 kg
Gradeability	45%
Turning Radius (Inside)	3.05 m
Turning Radius (Outside)	6.22 m
Axle Oscillation	10.16 cm
Drive Speed (High speed)	4.8 km/h







SJ85 AJ Work Height (m)

Skyjack UK

Capacity

Tyre Type

Tyre Size

Diesel Engine

Fuel Tank Capacity

Hydraulic Reservoir

Maximum # of Persons

Unit 1, Maes-y-Clawdd Maesbury Road Industrial Estate Oswestry, Shropshire, SY10 8NN Tel: +44 (0) 1691 676235 Fax: +44 (0) 1691 676239 Email: info@skyjackeurope.co.uk

Skyjack France

74 Rue Sibert F-42400 Saint-Chamond France

227 / 340 kg

2/3

Grip lug foam-filled

18-625

55 kW

115 L

170 L

Tel. +33 (0) 4 78 73 53 32 Fax. +33 (0) 4 78 56 52 42

Skyjack Germany Därmannsbusch 2a

D-58456 Witten Germany Tel: +49 (0) 2302 20 26 909 Fax: +49 (0) 2302 20 25 671

Skyjack AB Sweden Agnesbergsvägen 28

424 38 Agnesberg Sweden Tel: +46 (0) 31 21 22 45 Fax: +46 (0) 31 787 65 10

www.skyjack.com